

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
6 October 2005 (06.10.2005)

PCT

(10) International Publication Number
WO 2005/093261 A3

(51) International Patent Classification⁷: **F04D 29/60**

(21) International Application Number:
PCT/ZA2004/000155

(22) International Filing Date:
10 December 2004 (10.12.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003/9329 10 December 2003 (10.12.2003) ZA

(71) Applicant and

(72) Inventor: VAN DEN BERG, Zacharias, Joseph
[ZA/ZA]; 9 Cooperskloof Street, 1786 Glenharvie (ZA).


(74) Agent: VAN DER MERWE, Andries, Petrus, Sch; P O
BOX 20301, 2522 Noordbrug (ZA).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KB, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: SUBMERSIBLY OPERABLE HIGH VOLUME AND LOW PRESSURE LIQUID TRANSFER EQUIPMENT



(57) Abstract: Submersibly installable and operable high volume and low pressure stirrer type liquid transferring equipment (10) comprises a rotor type stirrer (12) driven via a drive shaft (16) passing without making contact along a sleeve (18) rooting centrally in a housing (14) having a downwardly facing inlet (22) and a tangentially arranged outlet (24). As the casing (26) of the housing (14) is independent of the remainder of the equipment (10) it is fitted with elevating leg plates (30). Its operative location is accommodated by a location of equipment installation. The stirrer (12) is bolted to a drive assembly (36) via its shaft (16). The length of the sleeve (18) is established in conjunction with the circumstances of use of the equipment (10) to maintain the zone (20) encompassed by the housing (14) sealed from above by a liquid seal.



Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(88) Date of publication of the international search report:

10 November 2005